

TRIBO SAE 140 HYPERMAX is a mineral simple-composition gear oil for mild operating conditions (low loads and sliding velocities). It may be recommended for the lubrication of accessory equipment to be installed in special vehicles (reducers in auto cranes, mechanisms on garbage trucks, side lifting components, etc.) when operating at temperatures no lower than 0°C.

PRODUCT PROPERTIES:

- Protects gears against moisture, preventing corrosion and increasing transmission life.
- Excellent compatibility with bronze and copper elements of gearbox synchronizers, allowing for smoother gear changes.
- Prevents foam formation, maintaining constant lubrication of all components and preventing the fatigue wear characteristic of gears.
- Approved by most industrial vehicle manufacturers.



TOWARDS NEW HORIZON

HYPERMAX

PREMIUM MINERAL

SAE 140

API GL-4

PRODUCT SPECIFICATIONS SAE 140

SAE GRADE	140
API GRADE	GL4
DENSITY @ 15°C	0.909
VISCOSITY @ 40°C	370
VISCOSITY @ 100°C	26.8
VISCOSITY INDEX	97 MIN.
FLASH POINT	240
POUR POINT	-12

CREDENTIAL & SPECIFICATIONS

RENAULT TRANSMISSIONS (SAE 80W AND 90), MB 235.1 (SAE 80W AND 90), VW 726 (SAE 80W AND 90), ZF TE-ML 16A/17A/19A (SAE 90), ZF TE-ML 08/17A (SAE 80W), DAF TRANSMISSIONS (SAE 80W AND 90), IVECO TRANSMISSIONS (SAE 80W AND 90)



*Information and figures given herein are typical of current production and conform to specifications, slight variations may occur.

